

Q6 EDGE 2.0 WITH TB3 SEAT / iLEVEL / TILT

DEALERS DETAILS

Dealers Name			
Order Date			
Address			
	Postcode		
Phone		Email	
PO No		Order Ref	

DELIVERY DETAILS

Dealers Address			
	Postcode		
Quantum Specialist			
Ⓢ Clients Weight			

BASE MODEL

12 Colour Options
 Height Adj. Removable Arm Supports
 Centre Mount Foot Platform
 TB3 Seating
 Auto Buckle Lap Belt
 14" Flat Free Drive Tyres
 2" x 6" Flat Free Front Castors



2" x 6" Flat Free Rear Castors
 ATX Suspension System
 QLNE Control System
 2 x 62 ah Batteries
 4 Mph (6 Km/h) 4-Pole Motors
 Max User Weight: 21 st 6lbs. (136 kg)

Standard = Standard Factory Feature
 FOC = Select Instead of Standard Factory Feature

DRIVE WHEELS

3" x 14" Flat Free Black Tyres. <i>With matching colour wheel accents.</i>	Standard
3" x 14" Pneumatic Black Tyres. <i>With matching colour wheel accents.</i>	FOC

COLOURS

Back in Black	Standard	Red Corvette	FOC
Green Machine	FOC	Lemon Crush*	FOC
Midnight Blue	FOC	Night Train*	FOC
Electric Blue	FOC	Evolution Orange*	FOC
Pretty in Pink	FOC	Military Green*	FOC
Deep Purple	FOC	Grey Street*	FOC

* Extended lead-time.

Please download our free PQ-365 app to view colours and other product features in more detail.



SEAT PACKAGES - SEAT WIDTH

☐	12"-16"W.
☐	14"-16"W.
☐	16"-20"W
☐	20"-22"W
Set width at:	

SEAT PACKAGES - SEAT DEPTH

☐	12"-16"D.
☐	14"-16"D.
☐	16"-20"D
☐	20"-22"D
Set depth at:	

STEALTH SEAT CUSHIONS

☐	No Seat Cushion Required	FOC
☐	Simplicity G: General Use, Fluid Resistant Stealth-Tek Cover. <i>158.7 Kg weight limit.</i>	Standard
☐	Zen SP: Skin Protection, 4-way Stretch, Coolcore Cover. <i>160 Kg weight limit.</i>	FOC
☐	TRU-Comfort 2 SPP: Skin Protection, Positioning, 4-way Stretch Coolcore Cover. <i>158.7 Kg weight limit.</i>	FOC

Please note that seat cushions may not be available in all width and depth combinations. Refer to our Stealth Cushion Order Forms for size availability.

SEAT POSITIONING

☐	iLevel Powered Seat Lift & Tilt. <i>12" lift & 50° tilt. Up to 3.5 Mph drive speed while elevated. Uses 2 power options.</i>	Standard
Powered iLevel Lift & Tilt Seat to Floor Height. <i>From seat pan.</i>		☐ 17.5" ☐ 18.5" ☐ 19.5"

BACKREST SPECIFICATIONS

☐	TRU-Balance 3 Back Support System. <i>Select TB3 back options below. Ignore all 'Back Cane' options.</i>	Standard
☐	Back Canes Only System. <i>Not available with TB3 flip-back arm supports. Move directly to 'Back Cane Only Support Options' if selected.</i>	FOC

Select one option above. Both options above include a metal active contour back support shell, TRU-Comfort 2 back cushion, and a set of wedge inserts.

TB3 BACK SUPPORT

☐	Active Contour Back Support with TRU-Comfort 2 Back Cushion and Wedge Inserts. <i>Select size in Back Support Dimensions.</i>	Standard
--------------------------	---	----------

TB3 BACK SUPPORT POSTIONING

☐	TRU-Balance 3 Static Back. <i>Angle can be preset manually.</i>	Standard
☐	TRU-Balance 3 Flip-forward Back. <i>Not available with TB3 flip-back arm supports. Not suitable for occupied transport.</i>	FOC

BACK CANE ONLY SUPPORT

☐	Active Contour Back Support with TRU-Comfort 2 Back Cushion and Wedge Inserts. <i>Select size in Back Support Dimensions.</i>				Standard
Back Cane Only Support Positioning.		Tool Angle Adjustable. <i>85° to 120° in 5° increments.</i>			Standard
Back Cane Height. <i>From seat pan.</i>	☐ 16"H.	☐ 17"H.	☐ 18"H.	☐ 19"H.	☐ 20"H.
	☐ 21"H.	☐ 22"H.	☐ 23"H.	☐ 24"H.	☐ 25"H.

BACK SUPPORT DIMENSIONS

Compatible with TB3 and Back Canes options above. Ignore Back Support Dimensions if omit back support is selected in TB3 or Back Canes sections. Back Support can be +/- 4" of seat width with TB3 Back Support System, but must be same as seat width with Back Canes Only System unless -2" or -4" Endo Mounts have been selected.

Backrest Support Width Package.		12"-14"W.	14"-16"W.	16"-20"W.
		18"-22"W.	20"-24"W.	
Back Support Width.	12"W.	14"W.	16"W.	17"W.
	18"W.	19"W.	20"W.	21"W.
	22"W.	24"W.		
Back Support Height. <i>From seat pan.</i>	14"H. <i>12"W back only.</i>	15"H. <i>12"W back only.</i>	16"H.	17"H.
	18"H.	19"H.	20"H.	21"H.
	22"H.	23"H.	24"H.	25"H. <i>Not available with 24"W back.</i>
	26"H. <i>Not available with 24"W back.</i>	27"H. <i>Not available with 24"W back.</i>	28"H. <i>Not available with 24"W back.</i>	29"H. <i>Not available with 24"W back.</i>

ARM SUPPORTS

2-Post Flip-up Removable. <i>Adjustment range 9" to 13" from seat pan. Minimum seat depth 16".</i>	Standard
Paediatric Single Post Drop-in Removable. <i>Adjustment range 7.75"- 9.75" from seat pan. 10" pads only.</i>	FOC
Single Post Drop-in Removable. <i>Adjustment range 11"-17" from seat pan. Minimum seat depth 14".</i>	FOC
TB3 Flip-back. <i>Adjustment range 8"-16" from seat pan. Includes lateral in/out adjustment.</i>	FOC
Arm Support Pads.	10" Standard Standard 10" Waterfall. <i>Not with TB3 Flip-back</i> FOC
	14" Standard FOC 14" Waterfall. <i>Not with TB3 Flip-back</i> FOC

CENTRE MOUNTED LEG SUPPORTS

Manually Adjustable Centre Mount Foot Platform. <i>Minimum seat width 14".</i>	Standard
Paediatric Adj. Centre Mount Foot Platform. <i>12"-14" seat widths only.</i>	FOC
Lower Leg Extensions. <i>From seat pan.</i>	8"-12". <i>Paediatric centre mount only.</i> FOC 10"-16". Standard 13"-19". FOC
Foot Supports.	10"W x 6"D Split Foot Supports. <i>Paediatric centre mount only.</i> FOC
	10"W x 8"D Split Foot Supports. FOC 10"W x 11"D Split Foot Supports. Standard
Calf Support.	Individual Calf Pads. <i>6"W x 6"H.</i> Standard

INDIVIDUALLY MOUNTED LEG SUPPORTS

70° Swing-Away. <i>Flip-up footplates. Adj. range 12" to 15". Minimum seat width 15".</i>	FOC
Manual Elevating Swing-Away. <i>Flip-up footplates. Adj. range 15" to 20". Min. seat width 15".</i>	FOC

INDIVIDUALLY MOUNTED CONFIGURABLE LEG SUPPORTS

60° to 90° Tool Adjustable Swing-Away. <i>Angle & depth adjustable footplates 6"W x 8"D. Select lowers below. Minimum seat width 15"</i>	FOC
Lower Leg Extensions. <i>From seat pan.</i>	11"-13" FOC 13.5"-16.5" Standard 15.5"-19.5" FOC

Certain configurations may result in reduced ground clearance below footplates. Contact Quantum Technical for information.
Adjustment ranges above are from seat pan to foot supports. Individual leg supports are supplied with heel loops.

STEALTH HEAD SUPPORTS

☐	UniLink 8" Comfort Plus. <i>HMO475-17M / CP08CCFPM.</i>	FOC
☐	UniLink 10" Comfort Plus. <i>HMO475-17M / CP10CCFPM.</i>	Standard
☐	UniLink 14" Comfort Plus. <i>HMO475-17M / CP14CCFPM.</i>	FOC

Please visit stealthproducts.com for alternative head supports.

NON-EXPANDABLE CONTROLS

☒	QLNES Controls. <i>2 power option ready.</i>	Standard
Control Method.	☐ Hand Control. <i>Select position in Hand Control Mounts below.</i>	Standard
	☐ Attendant Control. <i>Hand control mounted at rear.</i>	FOC

HAND CONTROL MOUNTS

☐	Fixed.	Standard
☐	Basic swing-away.	FOC
Mounting Position.	☐ Left	☐ Right

SPEED PROGRAM & LIGHTS PACKAGE

☐	2-Pole Motors & 4 Mph Program with Lights and indicators.	Standard
☐	2-Pole Motors & 6 Mph Program with Lights and indicators.	FOC

ACCESSORIES

☐	Prepare Chassis for Dahl Docking System. <i>Dahl system not included.</i>	FOC
--------------------------	---	-----

NOTES & SPECIAL REQUESTS



Quantum®
 32 Wedgwood Road, Bicester,
 Oxon, OX26 4UL
 Phone: 01869 324600
 Fax: 01869 323070
 Email: sales@quantumrehab.co.uk
 Web: www.quantumrehab.co.uk
MOTABILITY ID 721026 - 01/04/25 V1

